
Check up to five results to perform an action.

## **Anaerobic Adhesives/Sealants Thread locking**

The **TORQUE THREADLOCKING SERIES** represents state of the art anaerobic technology, with world class performance.

The **TORQUE THREADLOCKING SERIES** is manufactured to provide specific viscosities, strengths, and cure speeds to meet any application requirement. These anaerobic resins prevent against vibration loosening, while locking and sealing threaded assemblies and metal parts. They have excellent resistance to extremely harsh environments.

**TORQUE THREADLOCKING** products are used in a wide range of assembly applications; from delicate electronic devices to heavy industrial equipment. They distribute the load on a fastener over the entire engagement length of the assembly, greatly reducing or completely eliminating fastener and material fatigue. They protect threaded areas by preventing rust and corrosion. These products significantly reduce production cost while enhancing the reliability of the finished product.



Results 1 - 10 of 10

Nobalio 1 10 01 10								
Item Name	Color	<u>Viscosity</u>	Temp. Range	<u>Cure</u> Speed (Fixture)	<u>Cure</u> Speed (Full)	Specific Gravity	MSDS	TDS
Torque Threadlockers	Violet	200 cps LT	-60 to 350 °F	10 min.	8 hours	1.08	MSDS	TDS
Torque Threadlockers	Purple	1200 cps MT	-60 to 350 °F	10 min.	8 hours	1.05	MSDS	TDS
Torque Threadlockers	Blue	200 cps LT	-60 to 350 °F	10 min.	8 hours	1.08	MSDS	TDS
Torque Threadlockers	Blue	1200 cps MT	-60 to 350 °F	10 min.	8 hours	1.07	MSDS	TDS
Torque Threadlockers	Blue	5000 cps MT	-60 to 350 °F	10 min.	8 hours	1.08	MSDS	TDS
Torque Threadlockers	Red	3500 cps MT	-60 to 350 °F	10 min.	8 hours	1.05	MSDS	<u>TDS</u>
Torque Threadlockers	Red	500 cps MT	-60 to 350 °F	10 min.	8 hours	1.12	MSDS	TDS
Torque Threadlockers	Red	9000 cps HT	-60 to 450 °F	15 min.	24 hours	1.11	MSDS	TDS
Torque Threadlockers	Red	7000 cps MT	-60 to 350 °F	10 min.	8 hours	1.12	MSDS	TDS
Torque Threadlockers	Green	12 cps LT	-60 to 350 °F	10 min.	8 hours	1.08	MSDS	<u>TDS</u>
	Torque Threadlockers	Torque Threadlockers	Torque Threadlockers Purple 1200 cps MT  Torque Threadlockers Blue 200 cps LT  Torque Threadlockers Blue 1200 cps LT  Torque Threadlockers Blue 5000 cps MT  Torque Threadlockers Red MT  Torque Threadlockers Red 500 cps MT  Torque Threadlockers Red MT	Torque Threadlockers Threadlockers Torque Threadlockers Threadlockers Threadlockers Torque Threadlockers Threadloc	Item Name         Color         Viscosity         Iemp. Range         Speed (Fixture)           Torque Threadlockers         Violet         200 cps LT         -60 to 350 °F         10 min.           Torque Threadlockers         Purple         1200 cps HT         -60 to 350 °F         10 min.           Torque Threadlockers         Blue         200 cps LT         -60 to 350 °F         10 min.           Torque Threadlockers         Blue         1200 cps HT         -60 to 350 °F         10 min.           Torque Threadlockers         Blue         5000 cps HT         -60 to 350 °F         10 min.           Torque Threadlockers         Red         MT         350 °F         10 min.           Torque Threadlockers         Red         500 cps HT         -60 to 450 °F         15 min.           Torque Threadlockers         Red         7000 cps HT         -60 to 450 °F         10 min.           Torque Threadlockers         Red         7000 cps HT         -60 to 60 to 70 min.         10 min.           Torque Threadlockers         Red         7000 cps HT         -60 to 70 min.         10 min.           Torque Threadlockers         Red         7000 cps HT         -60 to 70 min.         10 min.	Item NameColorViscosityIemp. RangeSpeed (Fixture)Speed (Full)Torque ThreadlockersViolet LT200 cps LT-60 to 350 °F10 min.8 hoursTorque ThreadlockersPurple MT1200 cps MT-60 to 350 °F10 min.8 hoursTorque ThreadlockersBlue LT200 cps LT-60 to 350 °F10 min.8 hoursTorque ThreadlockersBlue MT1200 cps MT-60 to 350 °F10 min.8 hoursTorque ThreadlockersBlue MT5000 cps MT-60 to 350 °F10 min.8 hoursTorque ThreadlockersRed MT3500 cps MT-60 to 350 °F10 min.8 hoursTorque ThreadlockersRed MT500 cps MT-60 to 350 °F10 min.8 hoursTorque ThreadlockersRed MT9000 cps MT-60 to 450 °F15 min.24 hoursTorque ThreadlockersRed MT7000 cps MT-60 to 350 °F10 min.8 hoursTorque ThreadlockersRed MT7000 cps MT-60 to 350 °F10 min.8 hours	Item Name         Color         Viscosity         Iemp. Range         Speed (Fixture)         Speed (Full)         Speed (Full)	Item Name         Color         Viscosity         Range         Speed (Fixture)         Speed (Full)         Speed (Full)         Speed (Full)         Speed (Full)         MSDS           Torque Threadlockers         Violet         200 cps LT         -60 to 350 °F         10 min.         8 hours         1.08         MSDS           Torque Threadlockers         Blue         200 cps LT         -60 to 350 °F         10 min.         8 hours         1.08         MSDS           Torque Threadlockers         Blue         1200 cps LT         -60 to 40 to 350 °F         10 min.         8 hours         1.07         MSDS           Torque Threadlockers         Blue         5000 cps MT         -60 to 40 to 350 °F         10 min.         8 hours         1.08         MSDS           Torque Threadlockers         Red         MT         350 °F         10 min.         8 hours         1.05         MSDS           Torque Threadlockers         Red         MT         350 °F         10 min.         8 hours         1.12         MSDS           Torque Threadlockers         Red         MT         350 °F         15 min.         24 hours         1.11         MSDS           Torque Threadlockers         Red         7000 cps MT         -60 to 40 min.         8 hours

1